

**Product Specification****Johnsonite Safe-T-First Cove Cap****1. PROPRIETARY PRODUCT/MANUFACTURER**

1.1. **Proprietary Product:** Resilient Safe-T-First Cove Cap Mouldings

**1.2. Manufacturer:**

Johnsonite, Inc.	Phone	(800) 899-8916
30000 Aurora Rd.		(440) 543-8916
Solon, Ohio 44139	Tech:	Ext 9297
Web: <a href="http://www.tarkettna.com">www.tarkettna.com</a>	Samples:	Ext 9299
Email: <a href="mailto:info@johnsonite.com">info@johnsonite.com</a>	Fax:	(440) 543-8920

**1.3. Proprietary Product Description:**

1.3.1. **Construction:** Johnsonite Safe-T-First Cove Cap Mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Johnsonite Safe-T-First Cove Cap Mouldings are designed for interior applications only.

**1.3.2. Styles:**

**PSCCN-99-B:** Resilient Cove Cap - Square top cap for 1/8" (3.18 mm) resilient covered sheet material. Cap extends 1/4" (6.35 mm) over covered material with 3/4" (1.91 cm) glue surface

**PCCCN-99-C:** Carpet Cove Cap - Square top cap for 1/4" (6.35 mm) covered carpet and wood paneling, 3/8" (9.53 mm) cap extends over covered material with 3/4" (1.91 cm) glue surface.

**1.3.3. Physical Characteristics:**

Length and Packaging:  
12 ft. (3.66 m) lengths, 10 pcs per carton

**2. PRODUCT PERFORMANCE AND TECHNICAL DATA**

- **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1
- **UL 1994 Certified** by Underwriters Laboratories, Inc.

**3. INSTALLATION**

See Moulding Installation and Maintenance instructions for complete details.

**3.1. Adhesives:****946 Premium Contact Adhesive**

Application: Brush

Approximate coverage:

1 kg Unit (0.95 Qt) – 24 to 36 sq. ft. per unit

6 kg Unit (1.44 Gal.) – 144 to 215 sq. ft. per unit

**4. AVAILABILITY AND COST**

Available through authorized Tarkett distributors nationwide.

**5. WARRANTY**

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

**6. MAINTENANCE**

Refer to Johnsonite Safe-T-First Resilient Mouldings Installation and maintenance Instructions for complete maintenance details.

**7. TECHNICAL SERVICES**

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the Contract Documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 800-899-8916.