

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** SureStart Underlayment delivers three key performance benefits: Quick installations, acoustical performance, and minimizes effect of substrate moisture. SureStart also mitigates surface imperfections and bridges small gaps/cracks in wood or concrete floors, eliminating fillers or skim coat repairs.

Note: SureStart is not recommended for use with heavy rolling loads.

1.2. Manufacturer:

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Technical Option 3
Web: www.tarkettna.com	Samples: Option 1
E-mail: info@johnsonite.com	

1.2.1. **Construction:** High-density synthetic rubber construction with superior acoustical sound reduction performance. **Note:** Aloft glue-down, Aloft Click, and Transcend Click flooring installed with SureStart requires the use of chair pads in workstations and similar castor wheel environments.

1.2.2. Styles/Sizes:

SureStart 36" (91.44 cm) wide Underlayment roll	
Product Number:	500033006
UPC:	033799334421
Width/Length:	36" x 33.33' (91.44 x 10.14 m)
Coverage per roll:	100 ft ² / 11.11 yd ² (9.2903 m ²)
Weight per roll:	29 lbs. (13.15 kg)

SureStart 54" (137.16 cm) wide Underlayment roll	
Product Number:	500033007
UPC:	033799334438
Width/Length:	54" x 44.4' (137.16 cm x 13.533 m)
Coverage per roll:	200 ft ² / 22.22 yd ² (9.2903 m ²)
Weight per roll:	58 lbs. (26.30 kg)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. Physical Characteristics:

- Density: 62 lbs./ft³ or 42 oz./yd²
- Thickness: 0.056"
- R-Value: 0.02
- Permeability (ASTM E96): < 1 perm
- Color: Green
- Castor Durability Test: Passes 25,000 cycles

2.2. Acoustical Data:

- ASTM E2179: Delta IIC 17 (over 6" concrete)

3. INSTALLATION

- Concrete must not exceed 99% RH in accordance with ASTM F2170, or 10 lbs MVER in accordance with ASTM F1869, and pH between 7 to 11.
- See Tarkett SureStart installation instructions for complete details.

4. AVAILABILITY

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

10 year Limited Light Commercial Warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

For click installations, immediate initial maintenance must be implemented.

For glue-down installations, 72 hours after installation is completed, initial maintenance procedures must be implemented.

Refer to the Tarkett flooring Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department
30000 Aurora Road, Solon, Ohio 44139
(800) 899-8916
Fax (440) 632-5643
email: info@johnsonite.com
www.tarkettna.com