


### 1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** SureStart Underlayment delivers three key performance benefits: Quick installations, acoustical performance, and minimizes effect of substrate moisture. SureStart also mitigates surface imperfections and bridges small gaps/cracks in wood or concrete floors, eliminating fillers or skim coat repairs.



Note: SureStart is not recommended for use with heavy rolling loads.

### 1.2. Manufacturer:

Tarkett Phone (800) 899-8916  
 30000 Aurora Rd.  
 Solon, Ohio 44139  
 Web: [www.tarkettna.com](http://www.tarkettna.com)  
 E-mail: [info@johnsonite.com](mailto:info@johnsonite.com)

- 1.2.1. **Construction:** High-density synthetic rubber construction with superior acoustical sound reduction performance. SureStart can be specified under Aloft, I.D Freedom, I.D. Inspiration, Transcend Sureset, Adaptt, Contour, Event, and Venue. Note: Aloft glue-down, Aloft Click, and Transcend Click flooring installed with SureStart requires the use of chair pads in workstations and similar castor wheel environments.

### 1.2.2. Styles/Sizes:

SureStart 36" (91.44 cm) wide Underlayment roll	
Product Number:	500033006
UPC:	033799334421
Width/Length:	36" x 33.33' (91.44 x 10.14 m)
Coverage per roll:	100 ft <sup>2</sup> / 11.11 yd <sup>2</sup> (9.2903 m <sup>2</sup> )
Weight per roll:	29 lbs. (13.15 kg)

SureStart 54" (137.16 cm) wide Underlayment roll	
Product Number:	500033007
UPC:	033799334438
Width/Length:	54" x 44.4' (137.16 cm x 13.533 m)
Coverage per roll:	200 ft <sup>2</sup> / 22.22 yd <sup>2</sup> (9.2903 m <sup>2</sup> )
Weight per roll:	58 lbs. (26.30 kg)

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

#### 2.1. Physical Characteristics:

- Density: 62 lbs./ft<sup>3</sup> or 42 oz./yd<sup>2</sup>
- Thickness: 0.056"
- R-Value: 0.02
- Permeability (ASTM E96): < 1 perm
- Color: Green
- Castor Durability Test: Passes 25,000 cycles
- Acoustical (ASTM E2179): ΔIIC 17 (Tested over 6 inch concrete)

### 3. INSTALLATION

- Concrete must not exceed 99% RH in accordance with ASTM F2170, or 10 lbs. MVER in accordance with ASTM F1869, and pH between 7 to 11.
- See Tarkett SureStart installation instructions for complete details.

### 4. AVAILABILITY

Available through authorized Tarkett distributors nationwide.

### 5. WARRANTY

10 year Limited Light Commercial Warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### 6. MAINTENANCE

For click installations, immediate initial maintenance must be implemented.

For glue-down installations, 72 hours after installation is completed, initial maintenance procedures must be implemented.

Refer to the Tarkett flooring Maintenance Instructions for complete maintenance details.

### 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.tarkettna.com](http://www.tarkettna.com) or contact Tarkett at 1-800-899-8916.