

1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** SureStart Underlayment delivers three key performance benefits: Quick installations, acoustical sound reduction, and moisture impermeability. SureStart also mitigates surface imperfections and bridges small gaps/cracks in wood or concrete floors, eliminating fillers or skim coat repairs.

Note: SureStart is not recommended for use with heavy rolling loads.

1.2. Manufacturer:

| | |
|--|-----------------------|
| Tarkett | Phone: (800) 899-8916 |
| 30000 Aurora Rd. | (440) 543-8916 |
| Solon, Ohio 44139 | Tech: Ext 9297 |
| Web: www.tarkettna.com | Samples: Ext 9299 |
| E-mail: info@johnsonite.com | |

- 1.2.1. **Construction:** Impermeable high-density synthetic rubber construction with superior acoustical sound reduction performance. **Note:** Aloft glue-down flooring installed with SureStart requires the use of chair pads in workstations and similar castor wheel environments.

1.2.2. Styles/Sizes:

| SureStart 36" (91.44 cm) wide Underlayment roll | |
|---|--|
| Product Number: | 500033006 |
| UPC: | 033799334421 |
| Width/Length: | 36" x 33.33' (91.44 x 10.14 m) |
| Coverage per roll: | 100 ft ² / 11.11 yd ² (9.2903 m ²) |
| Weight per roll: | 29 lbs. (13.15 kg) |

| SureStart 54" (137.16 cm) wide Underlayment roll | |
|--|--|
| Product Number: | 500033007 |
| UPC: | 033799334438 |
| Width/Length: | 54" x 44.4' (137.16 cm x 13.533 m) |
| Coverage per roll: | 200 ft ² / 22.22 yd ² (9.2903 m ²) |
| Weight per roll: | 58 lbs. (26.30 kg) |

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. Physical Characteristics:

- Density: 62 lbs./ft³ or 42 oz./yd²
- Thickness: 0.056"
- R-Value: 0.02
- Color: Green
- Castor Durability Test: Passes 25,000 cycles

2.2. Acoustical Data:

- ASTM E492 & E989: IIC 66
- ASTM E2179: Delta IIC 17
- ASTM E90 / 413: STC 63

2.3. Fire Resistance (ASTM E 648/NFPA 253 Critical Radiant Flux): Class 1

3. INSTALLATION

- Concrete must not exceed 90% RH in accordance with ASTM F2170 or 8lbs MVER in accordance with ASTM F1869.
- See Tarkett SureStart installation instructions for complete details.

4. AVAILABILITY

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

For click installations, immediate initial maintenance must be implemented.

For glue-down installations, 72 hours after installation is completed, initial maintenance procedures must be implemented.

Refer to the Tarkett flooring Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.