



# JOHNSONITE RESILIENT MOULDINGS

## Cove Filler Strips

## Product Specification

### 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Resilient Cove Filler Strip Mouldings

1.2. **Manufacturer:**

Tarkett	Phone: (800) 899-8916
30000 Aurora Rd.	(440) 543-8916
Solon, Ohio 44139	Tech: Ext 9297
Web: <a href="http://www.tarketta.com">www.tarketta.com</a>	Samples: Ext 9299
E-mail: <a href="mailto:info@johnsonite.com">info@johnsonite.com</a>	

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Johnsonite Cove Filler Strip mouldings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality fillers, and colorants. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Not recommended for commercial kitchen environments.

1.3.2. **Styles:**

**CFS-00:** 1-3/4" (4.45 cm) radius filler strip for covered sheet goods, 1-1/2" (3.81 cm) long wall and floor mounting surface

**CFS-00-A:** 1-1/4" (3.18 cm) radius filler strip for covered sheet goods, 7/8" (2.22 cm) long wall and floor mounting surface

**CFS-00-M:** 1/2" (12.7 mm) radius filler strip for covered sheet goods, 1" (2.54 cm) long wall and floor mounting surface

1.3.3. **Physical Characteristics**

Length:

CFS-00 and CFS-00-A = 12 ft. (3.66 m)

CFS-00-M = 5 ft. (1.52 m)

Packaging:

CFS-00 - 12 lengths per carton.

CFS-00-A - 32 lengths per carton

CFS-00-M – 50 lengths per carton.

### 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- Hardness - ASTM D 2240 - Not less than 85 Shore A
- Abrasion Resistance - ASTM D 3389 - 0.22 mg/cycle
- Fire Resistance: ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

### 3. INSTALLATION

See Resilient Moulding Installation instructions for complete details.

3.1. **Adhesives:**

Porous and Nonporous Substrates:

**Johnsonite #946 Premium Contact Bond Adhesive**

Application: Brush or roller

Approximate coverage:

1 kg Unit (0.95 Qt.) – 24 to 36 Sq. Ft. per Unit

6 kg Unit (1.44 Gal.) – 144 to 215 Sq. Ft. per Unit

### 4. AVAILABILITY AND COST

Available through authorized Johnsonite distributors nationwide.

### 5. WARRANTY

Limited 2 year warranty. For complete details, contact Johnsonite or an authorized Johnsonite distributor.

### 6. MAINTENANCE

None required

### 7. TECHNICAL SERVICES

**Samples:** Submittal samples for verification and approval available upon request from Johnsonite. Samples shall be submitted in compliance with the requirements of the Contract Documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at [www.johnsonite.com](http://www.johnsonite.com) or contact Johnsonite at 800-899-8916.



**Technical Services Department**  
 30000 Aurora Road, Solon, Ohio 44139  
 (800) 899-8916 ext 9297  
 Fax (440) 632-5643  
 email: [info@johnsonite.com](mailto:info@johnsonite.com)  
[www.tarketta.com](http://www.tarketta.com)