

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Resilient Vinyl Stair Nosings

1.2. Manufacturer:

Tarkett Phone: (800) 899-8916
 30000 Aurora Rd. (440) 543-8916
 Solon, Ohio 44139 Tech: Ext 9297
 Web: www.tarkettna.com Samples: Ext 9299
 E-mail: info@johnsonite.com

1.3. Proprietary Product Description:

1.3.1. **Construction:** Johnsonite Vinyl Stair Nosings are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants to meet the performance requirements of ASTM F-2169 Standard Specification for Resilient Stair Treads, Type TV, Class 1 and 2, Group 1 and 2. Johnsonite Vinyl Stair Nosings are available with a 2" (5.08 cm) wide co-extruded strip of contrasting color. Standard formulation exceeds ASTM E 648 Class 1 Flammability requirements. Johnsonite Vinyl Stair Nosings are designed for interior applications only and not recommended for commercial kitchen environments.

1.3.2. Styles:

Visually Impaired

- **VIRC-XX-A** Visually Impaired Recessed Vinyl Stair Nosing, 2" (5.08 cm) hinged square nose configuration, 3-1/8" (7.94 cm) tread depth with 2" (5.08 cm) wide co-extruded contrasting color strip, undercut for 1/4" (6.35 mm) to 5/16" (7.94 mm) carpet, for solid color without co-extruded color strip specify **SRCN-A**
- **VIRC-XX-B** Visually Impaired Recessed Vinyl Stair Nosing, 2" (5.08 cm) hinged square nose configuration, 3" (7.62 cm) tread depth with 2" (5.08 cm) wide co-extruded contrasting color strip, undercut for 1/8" (3.17 mm) resilient or 3/16" (4.76 mm) butt with lip removed, for 2" contrasting color grit strip specify **VIRC-B2**, for solid color without co-extruded color strip specify **SRCN-B**
- **VITSN-XX-** Visually Impaired Top Set Vinyl Stair Nosing 2" (5.08 cm) square nose configuration, 3" (7.62 cm) tread depth with 2" (5.08 cm) wide co-extruded contrasting color strip, top-setting on concrete, steel, and wood steps to enhance visibility
- **VIVCD-XX** Visually Impaired Double Undercut Carpet Vinyl Stair Nosing, 2" (5.08 cm) hinged square nose configuration 3-3/16" (8.10 cm) tread depth with 2" (5.08 cm) wide co-extruded contrasting color strip, undercut for 1/4" (6.35 mm) to 5/16" (7.94 mm) carpet on step and riser, for solid color without co-extruded color strip specify **SVCD**

Non-visually Impaired

- **DTN-XX** Top Set Vinyl Stair Nosings for residential use, 1-3/4" (4.45 cm) square nose with 1-3/4" (4.45 cm) tread depth
- **VCD-XX** Double Undercut Carpet Vinyl Stair Nosing, 1-5/16" (2.85 cm) tread depth, 1-9/16" (3.10 cm) hinged square nose configuration, undercut for 1/4" (6.35 mm) to 5/16" (7.94 mm) carpet on step and riser
- **RCN-XX-A** Undercut Carpet Vinyl Stair Nosing, 1-15/16" (4.92 cm) tread depth, 2" (5.08 cm) hinged square nose configuration, undercut for 1/4" (6.35 mm) to 5/16" (7.94 mm) carpet
- **RCN-XX-B** Recessed Vinyl Stair Nosing, 3" (7.62 cm) tread depth with ribbed surface, 2" (5.08 cm) hinged, square nose configuration, undercut for 1/8" (3.18 mm) material
- **SVCD-XX-A** Double Undercut Carpet Vinyl Stair Nosing, 3-1/8" (7.93 cm) tread depth, 1-1/2" (3.81 cm) hinged square nose configuration, undercut for 3/8" (9.53 mm) carpet on step and riser
- **SRCN-XX-C** Recessed Vinyl Stair Nosing, 2" (5.08 cm) hinged, square nose configuration, 3-1/8" (7.94 cm) tread depth, undercut for 3/8" (9.53 mm) carpet on step
- **VDL-XX-SQ** 2-1/16" (5.24 cm) tread depth, 2" (5.08 cm) hinged square nose configuration, butt edge for 1/8" (3.17 cm) resilient materials
- **VDL-XX-RD** 1-1/2" (3.75 cm) diameter round nose configuration, 2-1/16" (5.24 cm) tread depth, butt edge for 1/8" (3.17 cm) resilient materials

1.3.3. Physical Characteristics:

Lengths: 12 ft. (3.66 m), Packaging: 120 ft. (39.58 m) per carton, except VI and SRCN-A 72 ft. (21.95 m); VI and SVCD 60 ft (18.29 m); SVCD-A and SRCN-C 48 ft. (14.6 m)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 1.1. **Hardness** (ASTM D 2240): Not less than 85 Shore A
- 1.2. **Abrasion Resistance** (ASTM D 3389): < 1 gram weight loss
- 2.1. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .6 for flat surfaces
- 2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

STAIRWELL MANAGEMENT

Vinyl Nosings

Product Specification

3. INSTALLATION

3.1. See Stair Tread, Nosing, Riser, and Stringer installation instructions for complete details.

3.2. Adhesives:

- **Tarkett 946 Premium Contact Adhesive Coverage:**
Non-porous Substrate:
24 – 36 sq. ft. per 1 kg (0.95 quart) unit
144 – 215 sq. ft. per 6 kg (1.44 gallon) unit
- **Tarkett 930 Two-part Epoxy Nose Caulk Coverage:**
50 linear feet per 30 oz. cartridge
(Based on approximately ¼" bead size)

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures can be implemented. Refer to vinyl nosing maintenance instructions for complete details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.



THE ULTIMATE
FLOORING EXPERIENCE

Technical Services Department
30000 Aurora Road, Solon, Ohio 44139
(800) 899-8916 ext 9297
Fax (440) 632-5643
email: info@johnsonite.com
www.tarkettna.com