



Replay™ Recycled Rubber Multi-functional and Sports Flooring

Maintenance Instructions for Tiles and Rolls

A proper and regular maintenance program is important to preserve your flooring material. Develop a routine maintenance schedule, using the approved maintenance products listed in these instructions. Your maintenance schedule will be determined by the type and amount of floor traffic.

Initial and Deep Cleaning

***** Initial Cleaning should not be performed until 72 hours after installation. *****

1. Vacuum or sweep the floor with a broom to remove all loose dirt and grit. Remove any adhesive residue left from the flooring installation.
2. Use only TASKI Profi neutral pH cleaner.
3. Dilute the TASKI Profi cleaner by mixing 6 to 10 ounces per gallon of warm water.
4. Apply the cleaning solution on the flooring with a mop and allow to stand for 5 to 10 minutes. ***Do not let the solution dry.***

Note: When using an auto-scrubber machine to apply the cleaning solution to the flooring, disengage the squeegee and vacuum and apply the solution with the rotary brushes.

5. Scrub the flooring with a blue scrubbing pad or a 22-gauge soft nylon brush on a single-disc scrubbing machine (150 to 300 RPM). For smaller areas, use a deck brush to scrub the floor.
6. Remove the cleaning solution using a wet vacuum or mop.

Note: When using an auto-scrubber machine to remove the cleaning solution, engage the squeegee and vacuum to remove the cleaning solution.

7. Rinse the floor thoroughly with clean cold water.
8. Allow the floor to dry completely.

Note A: If a luster finish is desired, use TASKI Wiwax. Mix a solution of one-half TASKI Wiwax and one-half lukewarm water. Apply two coats of the Wiwax solution with a mop after the *initial* cleaning. Allow the Wiwax solution to dry completely between coats.

Routine Cleaning

Two options for commercial applications:

Note B: For all residential applications, apply two coats of TASKI Wiwax as outlined in *Note A* above and follow **Option 2** below for routine cleaning.

Option 1: Clean with a neutral pH cleaner

1. Vacuum or sweep the floor with a broom to remove all loose dirt and grit.
2. Use only TASKI Profi neutral pH cleaner.
3. Dilute the Profi cleaner by mixing 2 to 4 ounces per gallon of warm water.
4. Apply the cleaning solution on the flooring with a mop and allow to stand for 5 to 10 minutes. ***Do not let the solution dry.***

Note: When using an auto-scrubber machine to apply the cleaning solution to the flooring, disengage the squeegee and vacuum and apply the solution with the rotary brushes.

5. Scrub the flooring with a blue scrubbing pad or a 22-gauge soft nylon brush on a single-disc scrubbing machine (150 to 300 RPM). For smaller areas, use a deck brush to scrub the floor.
6. Remove the cleaning solution using a wet vacuum or mop.

Note: When using an auto-scrubber machine to remove the cleaning solution, engage the squeegee and vacuum to remove the cleaning solution.

7. Rinse the floor thoroughly with clean cold water.
8. Allow the floor to dry completely.

Option 2: Clean with a cleaner/maintainer

1. Vacuum or sweep the floor with a broom to remove all loose dirt and grit.
2. Use only TASKI Wiwax cleaner/maintainer.
3. Dilute the Wiwax cleaner/maintainer by mixing 2 to 4 ounces per gallon of warm water.
4. Apply the Wiwax solution on the flooring with a clean mop.

Note: When using an auto-scrubber machine to apply the cleaner/maintainer, use TASKI Combiplus cleaner/maintainer diluted 2 to 4 ounces per gallon of warm water. Make sure the squeegee, vacuum and rotary brushes are engaged.

5. Allow cleaner/maintainer to dry completely.

Note C: Floors being maintained with TASKI Wiwax may need to be stripped after long-term use.

Stripping Procedure

1. Vacuum or sweep the floor to remove any loose surface dirt or grit.
2. Select a recommended floor stripper: TASKI Linostrip.
3. Dilute the Linostrip by mixing according to the label instructions.
4. Apply a liberal amount of the stripping solution to the floor with a mop and allow to stand for 5 to 15 minutes. ***Do not let the solution dry.***
5. Scrub the flooring with a blue scrubbing pad or a 22-gauge soft nylon brush on a single-disc scrubbing machine (150 to 300 RPM). For smaller areas, use a deck brush to scrub the floor.
6. Remove the solution using a mop or wet vacuum.
7. Repeat the process if necessary.
8. Rinse the floor thoroughly with clean water and allow to dry completely.

To support our customers' maintenance program, Johnsonite recommends the use of TASKI cleaning products. For specific maintenance advice, please contact TASKI at 1-800-827-5487 (USA and Canada calls).

Johnsonite®

Technical Services Department
16910 Munn Road, Chagrin Falls, Ohio 44023
(800) 899-8916 ext 297 Fax (440) 543-8920
www.Johnsonite.com
E-mail: info @ Johnsonite.com

© 2006 Johnsonite, Inc. A Tarkett Company.