Azterra™ | The Azrock® Collection

DESCRIPTION
Azterra Vinyl Enhanced Tile is recommended for use in high traffic applications where a smooth surfaced, easily maintained, durable, long-wearing floor is required. Recommended areas of use are school offices, classrooms and corridors, commercial office areas, hospital lobbies, patient rooms and corridors, and retail stores. Made in the USA.

Technical Data	Standards	Azterra
Type of Floor Covering		Vinyl Enhanced Tile
Classification	ASTM F 1066	Meets Requirements
Polyurethane Reinforced		Tritonite
Total Thickness		1/8" (3.2 mm)
Static Load Limit	ASTM F 970†	400 psi (modified)
Tile Size Weight/sq. ft./m^2 Carton Quantity Carton Weight		12" x 12" (30.5 cm x 30.5 cm) 1.20 lbs sq. ft. (12.92 lbs. m^2) 45 tiles = 45 sq. ft. (4.18 m^2) 54 lbs (24.5 kg)
Flammability	ASTM E 648	Class 1 >0.45 CRF
Smoke Density	ASTM E 662	<450
Slip Resistance SCOF	ADA Compliant	
Chemical Resistance		Good
Colors		14
Warranty		10 Year LIMITED Warranty. See www.johnsonite.com for complete warranty information.
Maintenance		Reduced Finish Maintenance / 1-2 coats of finish*

* Depending upon use of the floor.
† Static load limit per ASTM 970 modified by specifying a higher load.

Please visit johnsonite.com for the most updated specifications, and installation, cleaning and maintenance instructions.

How to Order: AT-(XXX) Color Number

Sustainable Facts

Azterra	Possible LEED Point Contribution
Construction Waste Management ReStart® Reclamation Program MR 2	1-2
Recycled Content Pre-Consumer 23% Post-Consumer 6.6% MR 4	1-2
Regional Materials Manufactured in Florence, Alabama, an ISO 14001 facility MR 5	1-2
Indoor Air Quality Low Emitting materials EQ 4.3 FloorScore certified and meets CA 01350	1
Return on Investment Easy to clean, less waxing required Reduced water, detergent and energy costs Requires fewer man-hours to install	

SpraySmart

- Immediate Occupancy
- Reduce Install Time
- Environmentally Friendly

The Johnsonite system includes transitions and finishing borders (wall base) to complete your flooring design and installation.

www.johnsonite.com

SPEED SWATCH
800-558-2240

Johnsonite
A Tarkett Company
16910 Munn Road
Chagrin Falls, OH 44023
800-899-8916 or 440-543-8916

www.johnsonite.com

Johnsonite
A Tarkett Company

©2011 Johnsonite Inc. Printed in the USA 4/11

The contents of this document including, but not limited to, all text and images (Content) are owned by Johnsonite Inc. with all rights reserved unless otherwise noted. Any Content that is a trademark, logo, or service mark is also a registered and unregistered trademark of Johnsonite Inc. Your use of any Content without the written permission of Johnsonite Inc. is strictly prohibited.