



ADHESIVES

SpraySmart™ 901

Resilient Flooring Spray Adhesive

Standard Plus Homogeneous Sheet

SpraySmart™ 901

SpraySmart 901 is a solvent-free adhesive specifically formulated for installing the following Johnsonite® VCT, VET, SVT, Vinyl Sheet, Rubber Tile products and Finishing Accessories:

- | | | | |
|--|--|--|--|
| VCT <ul style="list-style-type: none"> Azrock™ VCT (Solids & Feature Strips) Textile™ VCT VCT Basketball Kit | VET-SVT <ul style="list-style-type: none"> Azterra™ Color Essence™ Color Essence SR™ Gemstone™ Cortina Grande™ Cortina Grande SR™ Karim Kolors Karim Shapes | Vinyl Sheet <ul style="list-style-type: none"> Acczent® Acczent® Flourish Acczent® Wood Acoustiflor® Acczent® Wood Safe-T Aria™ iQ™ Granit™ iQ™ Granit™ Safe-T iQ™ Granit™ Micro Marbled Safe-T Melodia™ iQ™ Natural iQ™ Optima® iQ™ Optima® Acoustiflor® Standard Plus | Rubber Tile* <ul style="list-style-type: none"> Circulinity™ Collection Defiant™ Folio™ Collection Inertia™ Mesto™ Mesto Configurations™ MicroTone™ Minerality™ Prima® Marbleized & Olio® Triumph Replay® Tile & Sheet |
|--|--|--|--|

*Not approved for Eco-Shell™ with Cork, CorkTones™ or Metallurgy™ at this time

SpraySmart 901 uses an advanced spray adhesive technology that promotes improved productivity and indoor air quality, and provides occupational health and safety benefits. A unique water-based acrylic adhesive, SpraySmart 901 is available in easy-to-use, fully recyclable spray cans which utilize a safe, non-ozone depleting propellant.

SpraySmart 901 is an environmentally friendly, non-toxic, non-flammable intelligent adhesive option, enabling immediate occupancy; an important benefit for healthcare, education, retail and other environments where immediate foot and rolling traffic are required.

Technical Data	Standards	SpraySmart 901 Flooring Adhesive
Adhesive Type		Water-based Acrylic Blend
Appearance		Light Blue
Odor		Sweet Mild Odor
Flash Point		> 212° F
NFPA 704 Flammability Rating		0 - Non-flammable
Storage		Store Between 50° F & 120° F
Shelf Life		2 Years (If unopened)
Open Time		25-45 Minutes
Working Time		2 Hours
VOC Content		< 0.0 g/ml Calculated
Foot Traffic Permitted		Immediately After Installation
Heavy Rolling Traffic Permitted		Immediately After Installation
pH Tolerance	ASTM F710	11 pH
Substrate Moisture Tolerance	ASTM F2170 ASTM F1869	90% RH 8 lbs. per 1,000 ft.2 / 24 hrs.
Underfloor Heating Systems		Yes
Please visit www.tarkettna.com for the most updated specifications and installation, cleaning and maintenance instructions.		

Sustainability Facts	
To learn more, visit www.tarkettna.com .	
SpraySmart 901	LEED Credits Contribution
Construction Waste Management ReStart® Reclamation Program MR 2	1-2
Material Reuse Supports Reuse & Recycling of Flooring MR 3	1-2
Regional Materials Manufactured in Dalton, GA - an ISO 9001 Facility MR 5	1-2
People-Friendly Spaces Low-emitting Materials IEQ 4.1 Adhesives, FloorScore™ Certified & Meets CA 01350	1
Return On Investment Requires Fewer Man Hours to Install	

COVERAGE:
All flooring types listed porous & non-porous surfaces

VCT:
200 sq. ft./22 oz. can;
1,200 sq. ft./carton

VET-SVT:
160 sq. ft./22 oz. can;
960 sq. ft./carton

Vinyl Sheet:
150 sq. ft./22 oz. can;
900 sq. ft./carton

Rubber Tile:
80 sq. ft./22 oz. can;
4800 sq. ft./carton

SpraySmart™	
Immediate Traffic After Installation, Including Rolling Loads	✓
For Use Under Hospital Beds	✓
Eliminates Trowel Marks	✓
Heat Weld Immediately	✓
Increased Limits for Moisture and pH	✓
Reduces Adhesive Consumption	✓
Supports Reuse and Recycling of Flooring	✓
Cradle to Cradle - Silver Certification	✓

